tp-link

TP-Link TL-MR6400 router wireless Fast Ethernet Banda singola (2.4 GHz) 4G Nero

Marchio : TP-Link

Codice prodotto: TL-MR6400 V4

Nome del prodotto : TL-MR6400

TP-Link TL-MR6400. Tipo di connessione WAN: RJ-45. Banda Wi-Fi: Banda singola (2.4 GHz), Wi-Fi standard: Wi-Fi 4 (802.11n), Intervallo di trasferimento dei dati WLAN (max): 300 Mbit/s. Tipo di interfaccia LAN Ethernet: Fast Ethernet, Velocità trasferimento Ethernet LAN: 10,100 Mbit/s, Tecnologia di cablaggio: 10/100Base-T(X). Generazione di reti mobili: 4G, Standard 2G: Edge, GPRS, GSM, Standard 3G: HSPA+, UMTS. Algoritmi di sicurezza supportati: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK, Sicurezza firewall: DoS, SPI Firewall, IP and MAC Address Binding

WAN connection

Ethernet WAN *	✔
DSL WAN *	✘
SIM card slot *	✔
3G/4G USB modem compatibility *	✘
WAN connection type	RJ-45

Wireless LAN features

Wi-Fi band *	Single-band (2.4 GHz)
Top Wi-Fi standard *	Wi-Fi 4 (802.11n)
WLAN data transfer rate (max) *	300 Mbit/s
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)

Network

Ethernet LAN *	✔
Ethernet LAN interface type *	Fast Ethernet
Ethernet LAN data rates	10,100 Mbit/s
Cabling technology	10/100Base-T(X)
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3u
Port forwarding	✔
Port triggering	✔
Dynamic DNS (DDNS)	✔
Number of guest networks (2.4 GHz)	1
VPN server	PPTP VPN, IPSec VPN , OpenVPN
VPN Passthrough	✔
VPN support	PPTP, L2TP, IPSec

Mobile network

Mobile network generation	4G
3G	✔
4G	✔
2G standards	Edge, GPRS, GSM

Protocols

DHCP client	✔
DHCP server	✔
Universal Plug and Play (UPnP)	✔
Supported network protocols	IPv4, IPv6

Design

Product colour	Black
Indication light	✔
LED indicators	✔
On/off switch	✔
Product type *	Tabletop router

Certificates

Certification	CE, FCC, RoHS

Packaging content

Cables included	LAN (RJ-45)
AC adapter included	✔
Quick installation guide	✔
Quick start guide	✔

Antenna

Antenna design *	Internal & external
Antennas quantity	4
Detachable antenna(s)	✔

Power

Power source type *	DC
Output voltage	12 V
Output current	1 A

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-40 - 70 °C

Mobile network

3G standards	HSPA+, UMTS
4G standard	LTE
GSM bands supported	850,900,1800,1900 MHz
UMTS bands supported	900,2100 MHz
4G bands supported	800,900,1800,1900 MHz

Ports & interfaces

Ethernet LAN (RJ-45) ports *	4
USB port *	✗
Memory card slot(s)	✗
DC-in jack	✔

Management features

Web-based management	✔
Wi-Fi Multimedia (WMM)/(WME)	✔
Quality of Service (QoS) support	✔
Reset button	✔
WPS push button	✔

Security

Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
Firewall	✔
Firewall security	DoS, SPI Firewall, IP and MAC Address Binding
Guest access	✔
Access Control List (ACL)	✔
Stateful Packet Inspection (SPI)	✔
DoS attack prevention	✔
Parental control	✔
DMZ support	✔
Network address translation (NAT)	✔

Operational conditions

Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

System requirements

Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows Vista, Windows XP
Linux operating systems supported	✔
Mac operating systems supported	macOS

Weight & dimensions

Width	202 mm
Depth	141 mm
Height	33.5 mm

Packaging data

Package width	307 mm
Package depth	223 mm
Package height	70 mm
Package weight	600 g

Logistics data

Harmonized System (HS) code	85176990

Other features

Mobile network connection	✔
WLAN data transfer rates supported	11,54,300 Mbit/s
Bandwidth (first)	2.4 GHz
Supported WAN type	RJ-45 SIM
Frequency band	2.4 GHz
Rack mounting	✔
xDSL connection	✗

6935364092771

6935364092764

6935364099923

6935364086848