



## TP-Link TL-WR840N router wireless Fast Ethernet Banda singola (2.4 GHz) Grigio, Bianco

**Marchio** : TP-Link

**Codice prodotto**: TL-WR840N

**Nome del prodotto** : TL-WR840N

TP-Link TL-WR840N. Tipo di connessione WAN: RJ-45. Banda Wi-Fi: Banda singola (2.4 GHz), Wi-Fi standard: Wi-Fi 4 (802.11n), Intervallo di trasferimento dei dati WLAN (max): 300 Mbit/s. Tipo di interfaccia LAN Ethernet: Fast Ethernet, Velocità trasferimento Ethernet LAN: 10,100 Mbit/s, Tecnologia di cablaggio: 10/100Base-T(X). Algoritmi di sicurezza supportati: WEP, WPA, WPA-Enterprise, WPA2, WPA2-Enterprise, Sicurezza firewall: SPI. Protocolli di rete supportati: IPv4, IPv6



<b>WAN connection</b>		<b>Protocols</b>	
Ethernet WAN *	✓	Supported network protocols	IPv4, IPv6
DSL WAN *	✗	<b>Design</b>	
SIM card slot *	✗	Product colour	Grey, White
3G/4G USB modem compatibility *	✗	LED indicators	✓
WAN connection type	RJ-45	On/off switch	✓
<b>Wireless LAN features</b>		Product type *	Tabletop router
Wi-Fi band *	Single-band (2.4 GHz)	<b>Certificates</b>	
Top Wi-Fi standard *	Wi-Fi 4 (802.11n)	Compliance certificates	RoHS, Federal Communications Commission (FCC), CE
WLAN data transfer rate (max) *	300 Mbit/s	<b>Packaging content</b>	
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Cables included	LAN (RJ-45)
<b>Network</b>		AC adapter included	✓
Ethernet LAN *	✓	Quick installation guide	✓
Ethernet LAN interface type *	Fast Ethernet	<b>Sustainability</b>	
Ethernet LAN data rates	10,100 Mbit/s	Sustainability compliance	✓
Cabling technology	10/100Base-T(X)	<b>Antenna</b>	
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3, IEEE 802.3u	Antenna design *	External
Port forwarding	✓	Antenna gain level (max)	5 dBi
Port triggering	✓	Antennas quantity	2
Number of guest networks (2.4 GHz)	1	<b>Features</b>	
VPN support	PPTP, L2TP, IPSec	Built-in processor	✓
Receiver sensitivity	270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER	Processor cores	1
		<b>Power</b>	
		Power source type *	DC
		Output voltage	9 V

<b>Ports &amp; interfaces</b>		<b>Power</b>	
Ethernet LAN (RJ-45) ports *	4	Output current	0.6 A
USB port *	✗	<b>Operational conditions</b>	
DC-in jack	✓	Operating temperature (T-T)	0 - 40 °C
<b>Management features</b>		Storage temperature (T-T)	-40 - 70 °C
Web-based management	✓	Operating relative humidity (H-H)	10 - 90%
Quality of Service (QoS) support	✓	Storage relative humidity (H-H)	5 - 90%
Reset button	✓	<b>System requirements</b>	
WPS push button	✓	Windows 2000, Windows 2000 Professional, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64	
<b>Security</b>		Windows operating systems supported	✓
Security algorithms	WEP, WPA, WPA-Enterprise, WPA2, WPA2-Enterprise	Mac operating systems supported	✓
Firewall	✓	<b>Weight &amp; dimensions</b>	
Firewall security	SPI	Width	182 mm
Guest access	✓	Depth	128 mm
Filtering	✓	Height	35 mm
MAC address filtering	✓	<b>Packaging data</b>	
URL filtering	✓	Package width	265 mm
DMZ support	✓	Package depth	180 mm
<b>Protocols</b>		Package height	86 mm
DHCP client	✓	Package weight	430 g
DHCP server	✓	<b>Other features</b>	
Universal Plug and Play (UPnP)	✓	WLAN data transfer rates supported	11,54,300 Mbit/s



0115971613347



115971613347



6935364070533

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.