



TP-Link CPE210 300 Mbit/s Bianco Supporto Power over Ethernet (PoE)



Marchio : TP-Link

Codice prodotto: CPE210 V3.20

Nome del prodotto : CPE210

TP-Link CPE210. 2.4 GHz, Velocità massima di trasferimento dati: 300 Mbit/s. Algoritmi di sicurezza supportati: AES, TKIP, WPA, WPA-PSK, WPA2, WPA2-PSK. Supporto Power over Ethernet (PoE). Colore del prodotto: Bianco

Features		Design	
2.4 GHz *	✓	Placement *	Pole
5 GHz *	✗	Product colour *	White
6 GHz *	✗	International Protection (IP) code	IPX5
Maximum data transfer rate *	300 Mbit/s	Reset button	✓
Frequency band	2.4 - 2.483 GHz	LED indicators	Status
Networking standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Antenna	
Automatic channel selection	✓	Antenna type *	Internal
Automatic channel scanning	✓	Antenna direction type	Directional
MIMO	✓	Antenna gain level (max)	9 dBi
VLAN support	✓	Polarization	Dual polarization
Wireless isolation	✓	Performance	
Dynamic Frequency Selection (DFS)	✓	Built-in processor	✓
Maximum outdoor range	5000 m	Processor model	Qualcomm Atheros
Security		Processor frequency	560 MHz
Security algorithms *	AES, TKIP, WPA, WPA-PSK, WPA2, WPA2-PSK	Processor architecture	MIPS 74Kc
MAC address filtering	✓	Flash memory	8 MB
Service Set Identifier (SSID) features	SSID broadcast, SSID broadcast on/off	Internal memory	64 MB
IGMP snooping	✓	Certificates	
Auto Wireless Distribution System (WDS)	✓	Certification	CE/FCC/UL/IC/GS/PSB/C-tick/SAA/S-Mark/KC-mark CE, FCC, RoHS
Protocols		Weight & dimensions	
Universal Plug and Play (UPnP)	✓	Width	224 mm
Management features		Depth	79 mm
Web-based management	✓	Height	60 mm
Management platform	Pharos Control	Packaging data	
Firmware upgradeable	✓	Package width	132 mm
Ports & interfaces		Package depth	270 mm
Ethernet LAN (RJ-45) ports *	2	Package height	106 mm
		Package weight	760 g
		Packaging content	
		Quantity per pack	1 pc(s)
		Cables included	AC

Ports & interfaces		Packaging content	
DC-in jack	✓	Mounting kit	✓
Power		Operational conditions	
Power over Ethernet (PoE) *	✓	Operating relative humidity (H-H)	10 - 90%
Power over Ethernet (PoE) type supported	Passive PoE	Operating temperature (T-T)	-30 - 70 °C
AC input voltage	100 - 240 V	Storage temperature (T-T)	-40 - 70 °C
AC input frequency	50 - 60 Hz	Storage relative humidity (H-H)	5 - 95%
Output voltage	24 V		
Output current	0.25 A		



6935364071677

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 18-DEC-2024. Prints or copies of Information are only valid on the printed Publication date