


TP-Link TL-WA1201 punto accesso WLAN 867 Mbit/s Bianco Supporto Power over Ethernet (PoE)

Marchio: TP-Link Codice prodotto: TL-WA1201

Nome del prodotto : TL-WA1201







Features		Design	
2.4 GHz * 5 GHz *	<i>I</i>	Placement * Product colour *	Table White
6 GHz * Maximum data transfer rate * Maximum data transfer rate (2.4	X 867 Mbit/s	On/off switch Reset button WPS push button	<i>y y</i>
GHz) Maximum data transfer rate (2.4 GHz) Ethernet LAN data rates	10,100,1000 Mbit/s	Antenna Antenna type * Antennas quantity	External 4
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Performance	4
MIMO MIMO type Wi-Fi Multimedia (WMM)/(WME) VLAN support	Multi User MIMO	Compatible operating systems	Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1, 10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0, or other Java-enabled browser
Virtual LAN features	Multicast VLAN	Certificates	
Quality of Service (QoS) support Transmitting power (CE)	✓ 20 - 23 dBm	Compliance certificates	RoHS, Federal Communications Commission (FCC), CE
Transmitting power (FCC)	30 dBm	Weight & dimensions	
Security Security algorithms *	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Width Depth Height	225 mm 145.5 mm 37 mm
Service Set Identifier (SSID) features	Multiple SSIDs	Packaging data	
Auto Wireless Distribution System (WDS) Access Control List (ACL)	✓ ✓	Package width Package depth Package height Package weight	400 mm 255 mm 69 mm 860 q

Protocols		Packaging content	
Universal Plug and Play (UPnP)	✓	Quantity per pack	1 pc(s)
DHCP server	✓	AC adapter included	✓
DHCP client	✓	PoE adapter included	✓
IPv4 & IPv6 features	Dual stack IPv4/IPv6	Cables included	LAN (RJ-45)
Ports & interfaces		Quick start guide	✓
Ethernet LAN (RJ-45) ports *	1	Operational conditions	
Power		Operating relative humidity (H-H)	10 - 90%
Power over Ethernet (PoE) *	✓	Operating temperature (T-T) Storage temperature (T-T)	0 - 40 °C -40 - 70 °C
Power over Ethernet (PoE) type supported	Active PoE	Storage relative humidity (H-H)	10 - 90%
Output voltage	12 V	Sustainability	
Output current	1.5 A	Sustainability compliance	✓





845973084035

0845973084035



6935364084035

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.