

## **TP-Link Omada EAP670 punto accesso WLAN 5400 Mbit/s Bianco Supporto Power over Ethernet (PoE)**

Marchio : TP-Link

Famiglia del prodotto: Omada Codice prodotto: EAP670

Nome del prodotto : EAP670


TP-Link Omada EAP670. 2.4 GHz, 5 GHz, Velocità massima di trasferimento dati: 5400 Mbit/s, Velocità trasferimento Ethernet LAN: 2500 Mbit/s. Supporto Power over Ethernet (PoE). Colore del prodotto: Bianco





Features		Management features	
2.4 GHz *	v	Web-based management	✓
5 GHz *	<ul> <li>Image: A set of the set of the</li></ul>	Firmware upgradeable	<ul> <li>Image: A set of the set of the</li></ul>
6 GHz *	×	Power	
Maximum data transfer rate *	5400 Mbit/s	Power over Ethernet (PoE) *	1
Maximum data transfer rate (2.4 GHz)	574 Mbit/s	Input current	1.5 A
Maximum data transfer rate (5 GHz)	4804 Mbit/s	Design	
Ethernet LAN data rates	2500 Mbit/s	Placement *	Ceiling, Wall
Frequency band	2.4 - 5 GHz	Product colour *	White
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	International Protection (IP) code	IP67
		Reset button	<ul> <li>Image: A set of the set of the</li></ul>
Number of users	250 user(s)	LED indicators	<ul> <li>Image: A set of the set of the</li></ul>
Automatic channel selection	1	Antenna	
Automatic channel scanning	<ul> <li>Image: A set of the set of the</li></ul>	Antenna type *	Internal
МІМО	1	Antenna direction type	Omni-directional
MIMO type	Multi User MIMO	Antennas quantity	6
VLAN support	×	Antenna gain level (max)	5 dBi
Rate limiting	1	Certificates	
Wireless isolation	1	Certification	CE, FCC, RoHS
Band steering	1	Weight & dimensions	
Quality of Service (QoS) support	1	Width	243 mm
BeamForming	✓	Depth	243 mm
Transmitting power (CE)	<20 dBm(2.4 GHz, EIRP); <23 dBm(5 GHz, band1 & band2, EIRP); <30 dBm(5 GHz, band3, EIRP)	Height	64 mm
		Packaging data	
Transmitting power (FCC)	<25 dBm (2.4 GHz); <28 dBm (5 GHz)	Package width	302 mm
		Package depth	304 mm

Security		Packaging data	
Service Set Identifier (SSID) features	Multiple SSIDs	Package height Package weight	82 mm 1.32 kg
Number of SSID supported Remote Authentication Dial-In User Service (RADIUS)	16 ✓	Packaging content	
		Quantity per pack	1 pc(s)
Access Control List (ACL)	4	Logistics data	
		Harmonized System (HS) code	85176990









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.